## Replacing the Battery Pack Inside the Body

- Unscrew the body and then slide out the old battery pack BATCELL 21700x8.
- Insert the battery pack to follow the direction as per attached photo.



### Choosing between 4-Levels, Red and SOS of output

- Press the push button every time to choose the desired output level: I- output at 10%, II-output at 25%, III-output at 50%, IV-output at 100%.
- For 4-Levels setting, press the push button each time to change the level of output accordingly.
- For Red LED setting, two very short rapid presses of the button will switch to red light mode. Switch back to bright light mode with a slightly longer press and release.
- For SOS setting, press the push button for 2 sec to get SOS effect and back to normal when you press the push button once again.
- For OFF setting, press the push button one time after 1 sec of level selection or press the push button five times after 4-Levels setting.



## Battery level indicator built-in

• Color of LEDs change from the time being. It will change from blue to green and green to red. When the red led flashes, it reminds people to charge up the battery.



## **Charging the Battery**

- Plug the Smart Quick Charger's connector into the socket of the BATCELL21700x8 Li ion rechargeable battery pack.
- · Red light means charging in progress, green light means fully charged.



- There is no need to discharge after use.
- Charge time will depend on the remaining capacity in the battery and the surrounding temperature.

## **Setup Using Handle**

• The light comes with handle



## Maintenance and Transportation

- · After each dive, always rinse with fresh water. If the diving light will not be used for a prolonged period of time (more than a month), remove the battery from the light.
- In rare cases of flooding, discontinue use. Turn the light off immediately and rinse with fresh water. Let the components dry completely, and return it to Bigblue for service.
- Flooding damage cannot be repaired on site.

## Clean the light and Lubricate the O-Ring

- For good practice, put the light into fresh water for few hours after every dive.
- Dry it out and put the silicone crease on the O-Ring. Ready for other dive.

# Setup Using Photographic Arms and Clips\*

- Twist the knobs on the clips anticlockwise until loosened.
- Insert the ball joint of the Video Light in between the gaps of the clips.
- Once the ball joint is inserted into the clips, secure its position by twisting the knobs on the clips clockwise.



# **Technical Specifications**

Light Source Light Output

Light output (Red color mode) Casing Material

Power Source

Angle of Light Beam Color Temperature Color Rendering Index

Burn Time

Maximum Depth Size

Weight in Air Buoyancy in Sea water Switching System

Front Glass

COB LED + 10 x XPE Red LED 3000 Lm ( level I), 7500 Lm ( level II) 15000 Lm ( level III), 30000 Lm ( level IV) 1200 Lm

Aluminum alloy. Anti-corrosive anodized Li ion Rechargeable battery pack BATCELL 21700x8

160° wide beam

5000K

Ra 85 1.5 hrs (level IV), 3 hrs(level III)

6 hrs (level II) and 15 hrs (level I)

100m tested

Dia. 85 x L. 144.6mm 1391g (including battery)

-597g (including battery)

Push button with battery indicator Tempered optical glass

Specifications subject to change without prior notice

Li ion Rechargeable Battery Ultra Power LED Video Light with High Color Rendering Index



charger. Do not continue charging the cell. suggested by the mobilem is with the battery or the 3. If the battery does not charge in the approximate time

gets excessively warm.

Discontinue using charger and/or battery if the battery and plan to have someone be in attendance. unattended. Check the "time required to fully re-charge"

1 Never put your battery on a charger and leave it

## Charging Li ion battery

used for extended period of time battery and the surrounding temperature 10. Remove the battery from the light if it is not going to be

Charge time will depend on the remaining charge in the gischarged battery can damage the battery low battery capacity. Turning on the light with a fully

Do not turn on the light, if the light has turned off due to

The battery should then be disconnected.

Charge the battery after each use. It does not have to be discharged before charging. Should charge the battery every month even you don't use it.

Propositiving the light if the light has turned off due to positive and the light in the light has turned off due to the proposition.

Green light on the charger indicates fully charged battery. attempts, the battery does not function. again. If the red light does not light up after several

The red light on the charger will light up after a short time, indicating charging is taking place. If the red light does not light up, disconnect the battery and re-connect it counection can damage the unit

Make sure to connect with the correct polarity. Incorrect

Plug in the charger before you place the battery in the Fully charge the battery before using it first time. Use only the power adapter supplied with the charger.

# Li ion battery charge and care

Congratulations on your purchase of our Bigblue product. The Bigblue Diving Light uses carefully selected materials that have met rigorous industry standards. With innovative manufacturing processes, and strict quality controls, we guarantee the reliability of all Bigblue diving products.

#### Introduction

The CB 30000P II delivers a stunning 30000 lumens light output COB LED and 1200 lumens red light output 10 x high intensity red LED. It is a compact and versatile diving light with wide and even light beam, best suitable for video shooting. Combined with the self-contained BATCELL21700x8 Li ion rechargeable battery pack design, it actualizes the super convenience and performance which can meet the needs of discerning video professionals.



 External damage, such as being dropped or getting wet, can also cause a lithium-ion battery to fail. controlled and safe manner

extinguished, allow the pack to burn out on its own in a If the fire of a burning lithium-ion battery cannot be

from spreading. graphite, copper powder or soda (sodium achonate) to extinguish a lithium-ion fire. Only pour water to prevent the fire from spreading

cause physical injury.
Use a foam extinguisher, CO2, dry chemical, powdered
reachite.

• The electrolyte is highly flammable and battery rupture can excessively warm.

Discontinue using the battery and/or charger if the battery gets and approved charger.

penetrate with foreign objects, apply reverse polarity, expose to high temperature or disassemble packs and cells. Use only lithium-ion cells with a designated protection circuit appropriate the protection of t

 Do not short-circuit, overcharge, crush, drop, mutilate, electrical and electronic products.

household waste. Check with your local collection system for Do not dispose of your rechargeable battery with general disassemble or modify.

• Do not dispose of in fire. Do not heat, deform, solder, gswaged or subjected to shock,

Do not operate the battery or the charger if it has been use for an extended period of time.

Remove the battery from the light if it is not going to be in

metal objects to avoid short circuit.

• The Li ion battery should not be dropped or be subjected to strong mechanical shock.

• When storing or carrying the battery, avoid direct contact with saftery to leak or rupture.

pressure. If the temperature is too high, it may cause the

battery and the surrounding temperature. Do not charge near hot temperature, under direct sunlight, cover the charger with a blanket, or place under heavy Charge time will depend on the remaining charge in the

result in fire or electric shock Using incompatible adapters may damage the charger or

Use only the power adapters supplied with the charger.

• Fully charge the batteries before using for the first time. connection can damage the unit

• Connect with the correct polarity (+ and -) only, incorrect Intended to be used with the custom-made
 BATCELL21700x8 Li ion rechargeable battery pack only.

Using the rechargeable Li ion battery

performance enhances focusing Built-in red color led



cools off, power comes back on. above 70°C. As soon as the light on land, or exposure to temperatures bower in case of prolonged use by automatically cutting off its prevents the light from overheating · The thermal protection system

tocusing performance. little creatures and enhancing • Built in red LED for viewing shy

enabling you to charge in a few hours. comes with a smart charger, • Li ion rechargeable battery design

all internal parts, eliminating the risk of leakage.

power output levels, but it is also designed to be insulated from • The push button not only makes it easy to change between the

50%, 25% and 10% of total brightness.

The four levels power output lets you choose between 100%,

warmer colors of the underwater surrounding while diving.

• The 5000K warm white light reflects

30000 lumens

COB LED to provide

frequent bulb replacement. 50,000 hours, reducing the need for they guarantee a burn time of

The LEDs are maintenance-free,

shoot results. making it a must for the best video an 160° perfectly even light spot, • COB LED delivers 30000 lumens, and

Features

## **Limited Warranty**

- 1. Bigblue guarantees the proper operation of this product by the original retail purchaser under normal and intended use.
- 2. This warranty applies only to the original retail purchaser, which does not apply to commercial or rental use, nor is it transferable to third parties.
- 3. If the original retail purchaser detects defect in the materials or workmanship, return the product together with proof of purchase indicating the date of purchase to an authorized Bigblue dealer
- 4. The warranty covers a period of up to one (1) year from the date of purchase. Warranty for rechargeable battery pack is valid for six (6) months only.
- 5. This limited warranty is in lieu of all other warranties. No other person or party is authorized to assume for Bigblue any other liability in connection with the sales of this product.
- 6. This warranty will be voided if the product or any of its parts have been tempered with, repaired, modified, transformed, adapted or damaged without authorization by Bigblue.
- 7. This warranty does not cover parts subjected to normal wear and tear, including and is not limited to the following: O-rings, battery pack, front glass (surface scratch or damage on impact).
- 8. This warranty does not cover damages due to impact, use in chlorinated or polluted waters, and extended exposure to heat sources

#### **Bossk International Company Limited**

Tel: (852) 3568 0773

Email: customerservice@bigblue.com.hk Web: www.bigbluelights.com

www.bigblue.com.hk MADE IN CHINA Patent Pending



