Replacing the Battery Pack Inside the Body

• Unscrew the body and then slide out the old battery pack.



Choosing between 4-Levels, Red and SOS of output

- Press the push button every time to choose the desired output level: I- output at 10%, II-output at 25%, III-output at 50%, IV-output at 100%.
- For 4-Levels setting, press the push button each time to change the level of output accordingly.
- For Red LED setting, two very short rapid presses of the button will switch to red light mode. Switch back to bright light mode with a slightly longer press and release.
- For SOS setting, press the push button for 2 sec to get SOS effect and back to normal when you press the push button once again.
- For OFF setting, press the push button one time after 1 sec of level selection or press the push button five times after 4-Levels setting.



Battery level indicator built-in

 Color of LEDs change from the time being. It will change from blue to green and green to red. When the red led flashes, it reminds people to charge up the battery.



Charging the Battery

- Place the Li ion battery inside the USB Charger. There is no need to discharge after use.
- Charge time will depend on the remaining capacity in the battery and the surrounding temperature.





Maintenance and Transportation

- After each dive, always rinse with fresh water. If the diving light will not be used for a prolonged period of time (more than a month), remove the battery from the light.
- In rare cases of flooding, discontinue use. Turn the light off immediately and rinse with fresh water. Let the components dry completely, and return it to Bigblue for service.
- Flooding damage cannot be repaired on site.

Clean the light and Lubricate the O-Ring

- For good practice, put the light into fresh water for few hours after every dive.
- Dry it out and put the silicone crease on the O-Ring. Ready for other dive.

Mounting the Goodman Glove



Goodman Glove



Fix the glove on the light with the supplied screw



Tighten by pulling the velco

For Right Hand User

• Unscrew the piece and place it upside down.





Setup Using Photographic Arms and Clips*

- Twist the knobs on the clips anticlockwise until loosened.
- Insert the ball joint of the Video Light in between the gaps of the clips.
- Once the ball joint is inserted into the clips, secure its position by twisting the knobs on the clips clockwise.



*Photographic Arms and Clips are sold separately

Technical Specifications

Light Source Light Output

Light output (Red color mode) Casing Material Power Source

Angle of Light Beam Color Temperature

Burn Time

Maximum Depth Size Weight in Air Buoyancy in Sea water

Switching System

Front Glass Lanyard 6 x XML LED + 4 x XBD Red LED 620 Lm (level I), 1550 Lm (level II) 3100 Lm (level III), 6200 Lm (level IV) 300 Lm

Aluminum alloy. Anti-corrosive anodized Li ion Rechargeable battery pack BATCELL18650x3

120° wide beam

1.5hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15hrs (level I)

100m tested Dia. 50 x L. 126.6 mm

381g (including battery)
-163g (including battery)

Push button with battery indicator Tempered optical glass

Included

Specifications subject to change without prior notice



charger. Do not continue charging the cell. to determine if the problem is with the battery or the suggested by the manufacturer contact the manufacturer If the battery does not charge in the approximate time

dets excessively warm.

Discontinue using charger and/or battery if the battery and plan to have someone be in attendance. Never put your battery on a charger and leave it unattended. Check the "time required to fully re-charge"

Charging Li ion battery

used for extended period of time 10. Remove the battery from the light if it is not going to be battery and the surrounding temperature

discriming the best of the property of the perior of the period of the perior of the period of the perior of the period of the p discharged before charging. Should charge the battery

Charge the battery after each use. It does not have to be

affempts, the battery does not function.

Green light on the charger indicates fully charged battery.

The battery should then be disconnected. again. If the red light does not light up after several not light up, disconnect the battery and re-connect it indicating charging is taking place. If the red light does

The red light on the charger will light up after a short time, Make sure to connect with the correct polarity. Incorrect connection can damage the unit.

Plug in the charger before you place the battery in the

Use only the power adapter supplied with the charger.

Fully charge the battery before using it first time.

Li ion battery charge and care

Congratulations on your purchase of our Bigblue product. The Bigblue Diving Light uses carefully selected materials that have met rigorous industry standards. With innovative manufacturing processes, and strict quality controls, we guarantee the reliability of all Bigblue diving products.

Introduction

The VL 6200P delivers a stunning 6200 lumens light output 6 x ultra high intensity LED and 300 lumens red light output 4 x high intensity red LED. It is a compact and versatile diving light with wide and even light beam, best suitable for video shooting. Combined with the self-contained 18650x3 Li ion rechargeable battery design, it actualizes the super convenience and performance which can meet the needs of discerning video professionals.



controlled and safe manner.

If the fire of a burning lithium-ion battery cannot be extinguished, allow the pack to burn out on its own in a

from spreading

extinguish a lithium-ion fire. Only pour water to prevent the fire graphite, copper powder or soda (sodium carbonate) to • Use a foam extinguisher, CO2, dry chemical, powdered

canse buλειcai iulnix. • The electrolyte is highly flammable and battery rupture can excessively warm

Discontinue using the battery and/or charger if the battery gets and approved charger

Use only lithium-ion cells with a designated protection circuit penetrate with foreign objects, apply reverse polarity, expose to high temperature or disassemble packs and cells.

Do not short-circuit, overcharge, crush, drop, mutilate, ejectrical and electronic products.

household waste. Check with your local collection system for Do not dispose of your rechargeable battery with general

disassemble or modify. • Do not dispose of in fire. Do not heat, deform, solder,

Do not operate the battery or the charger if it has been damaged or subjected to shock. use for an extended period of time.

Remove the battery from the light if it is not going to be in strong mechanical shock.

The Li ion battery should not be dropped or be subjected to

battery to leak or rupture. When storing or carrying the battery, avoid direct contact with metal objects to avoid short circuit.

pressure. If the temperature is too high, it may cause the cover the charger with a blanket, or place under heavy

Do not charge near hot temperature, under direct sunlight, battery and the surrounding temperature.

result in fire or electric shock.

Charge time will depend on the remaining charge in the

Using incompatible adapters may damage the charger or Use only the power adapters supplied with the charger

Fully charge the batteries before using for the first time.

Connect with the correct polarity (+ and -) only, incorrect connection can damage the unit. BATCELL 18650x3 Li ion rechargeable battery pack only.

Using the rechargeable Li ion battery

Limited Warranty

- 1. Bigblue guarantees the proper operation of this product by the original retail purchaser under normal and intended use.
- 2. This warranty applies only to the original retail purchaser, which does not apply to commercial or rental use, nor is it transferable to third parties.
- 3. If the original retail purchaser detects defect in the materials or workmanship, return the product together with proof of purchase indicating the date of purchase to an authorized Bigblue dealer or Biablue.
- 4. The warranty covers a period of up to one (1) year from the date of purchase. Warranty for rechargeable battery pack is valid for
- 5. This limited warranty is in lieu of all other warranties. No other person or party is authorized to assume for Bigblue any other liability in connection with the sales of this product.
- 6. This warranty will be voided if the product or any of its parts have been tempered with, repaired, modified, transformed, adapted or damaged without authorization by Bigblue.
- 7. This warranty does not cover parts subjected to normal wear and tear, including and is not limited to the following: O-rings battery pack, front glass (surface scratch or damage on impact).
- 8. This warranty does not cover damages due to impact, use in chlorinated or polluted waters, and extended exposure to heat sources

Bossk International Company Limited

Tel: (852) 3568 0773

Email: customerservice@bigblue.com.hk

Web: www.bigbluelights.com www.bigblue.com.hk MADE IN CHINA Patent Pending



pands-free operation Goodman glove for



ocnaing performance Built in red color led enhances



As soon as the light cools off, power comes back on. prolonged us on land, or exposure to temperatures above 70°C. overheating by automatically cutting off its power in case of The thermal protection system prevents the light from

Sturdy glove for hands-free operation underwater.

focusing performance.

• Built in red LED for viewing shy little creatures and enhancing charger, enabling you to charge in a tew hours.

Li ion rechargeable battery design comes with a smart

insulated from all internal parts, eliminating the risk of the power output levels, but it is also designed to be

The push button not only makes it easy to change between

The four levels power output lets you choose between 100%, 50%, 25% and 10% of total brightness.

underwater surrounding while diving. The 6500K white light reflects the true vibrant colors of the

repiacement.

of 50,000 hours, reducing the need for frequent bulb The LEDs are maintenance-free, they guarantee a burn time

video shoot results.

120° perfectly even light spot, making it a must for the best • 6 x ultra high intensity LED delivers 6200 lumens, and an

Features



