

Replacing the Battery Pack Inside the Body

- Unscrew the body and then slide out the old battery pack BATCELLEOCANISTER.
- Insert the battery pack to follow the direction as per attached photo.



Choosing between ON and OFF



Backmount



Sidemount

Choosing between 3-Levels of wide beam, 3-Levels of narrow beam and Red output

- Press the push button every time to choose the desired output level : I-output at 25%, II-output at 50%, III-output at 100%.
- For 3-levels setting of wide beam, press the push button each time to change the level of output accordingly.
- For 3-levels setting of narrow beam, press the push button for 2 sec to get narrow beam effect. Repeat the same way to press the push button for 2 sec to change the level of output of narrow beam effect.
- For Red LED setting, two very short rapid presses of the button will switch to red light mode. Switch back to bright light mode with a slightly longer press and release.
- For OFF setting, press the push button one time after 1 sec of level selection or press the push button four times after 3-levels setting.



Battery level indicator built-in

- Color of LEDs change from the time being. It will change from blue to green and green to red. When the red led flashes, it reminds people to charge up the battery.



Charging the Battery

- Place the BATCELLEOCANISTER Li ion rechargeable battery pack inside the BATCHREOCANISTER.
- There is no need to discharge after use.
- Red light means charging in progress, green light means fully charged.
- Charge time will depend on the remaining capacity in the battery and the surrounding temperature.



Maintenance and Transportation

- After each dive, always rinse with fresh water. If the diving light will not be used for a prolonged period of time (more than a month), remove the battery from the canister.
- In rare cases of flooding, discontinue use. Turn the light off immediately and rinse with fresh water. Let the components dry completely, and return it to Bigblue for service.
- Flooding damage cannot be repaired on site

Clean the light and Lubricate the O-Ring

- For good practice, put the canister into fresh water for few hours after every dive.
- Dry it out and put the silicone crease on the O-Ring. Ready for other dive.

Technical Specifications

VTL7000P Max EOS Backmount

Light Source	9 x LED + 4 x XPE Red LED
Light Output	1750 Lm (level I), 3500 Lm (level II)
(Flood beam mode)	7000 Lm (level III)
Light Output	725 Lm (level I), 1450 Lm (level II)
(Spot beam mode)	2900 Lm (level III)
Light Output	500 Lm
(Red color mode)	
Casing Material	Aluminium alloy. Anti-corrosive anodized
Power Source	Li ion Rechargeable battery pack 3 x BATCELLEOCANISTER Each BATCELLEOCANISTER is 88.06 Wh Good for travelling
Angle of Light Beam	120° wide beam and 10° narrow beam
Color Temperature	6500K
Burn Time	8 hrs (level III), 16 hrs (level II) and 32 hrs (level I)
Maximum Depth	150 m tested
Size (Light head)	Dia. 63 x L. 90.5 mm
Size (Canister)	Dia. 68 x L. 290 mm
Weight in Air	462 g
(Light head)	
Weight in Air	2300 g
(Canister)	
Buoyancy in Seawater	-191 g
(Light head)	
Buoyancy in Seawater	-1186 g
(Canister)	
Switching System	Push button with battery indicator
(Light head)	
Switching System	Mechanical ON / OFF switch
(Canister)	
Cable length	1.3 meters
Front Glass	Tempered optical glass

VTL7000P Max EOS Sidemount

Light Source	9 x LED + 4 x XPE Red LED
Light Output	1750 Lm (level I), 3500 Lm (level II)
(Flood beam mode)	7000 Lm (level III)
Light Output	725 Lm (level I), 1450 Lm (level II)
(Spot beam mode)	2900 Lm (level III)
Light Output	500 Lm
(Red color mode)	
Casing Material	Aluminium alloy. Anti-corrosive anodized
Power Source	Li ion Rechargeable battery pack 3 x BATCELLEOCANISTER Each BATCELLEOCANISTER is 88.06 Wh Good for travelling
Angle of Light Beam	120° wide beam and 10° narrow beam
Color Temperature	6500K
Burn Time	8 hrs (level III), 16 hrs (level II) and 32 hrs (level I)
Maximum Depth	150 m tested
Size (Light head)	Dia. 63 x L. 90.5 mm
Size (Canister)	Dia. 68 x L. 290 mm
Weight in Air	462 g
(Light head)	
Weight in Air	2300 g
(Canister)	
Buoyancy in Seawater	-191 g
(Light head)	
Buoyancy in Seawater	-1186 g
(Canister)	
Switching System	Push button with battery indicator
(Light head)	
Switching System	Mechanical ON / OFF switch
(Canister)	
Cable length	1.3 meters
Front Glass	Tempered optical glass

VTL7000P MAX EOS BACKMOUNT / SIDEMOUNT

Li ion Rechargeable Battery High Power LED Video / Tech Light with E/O Cord Battery Canister



Sidemount
(23.8 Ah)




Backmount
(23.8 Ah)

Congratulations on your purchase of our Bigblue product. The Bigblue Diving Light uses carefully selected materials that have met rigorous industry standards. With innovative manufacturing processes, and strict quality controls, we guarantee the reliability of all Bigblue diving products.

Introduction

The VTL7000P Max EOS Backmount / Sidemount delivers a stunning 7000 lumens light output 6 x ultra high intensity LED and 500 lumens red light output 4 x high intensity red LED. It is a compact and versatile diving light with wide and even light beam, best suitable for video shooting. Also the light delivers 2900 lumens light output with narrow beam with strong penetrating hot spot, best suitable for technical diving as well. Combined with the self-contained BATCELLEOCANISTER Li ion rechargeable battery design, it actualizes the super convenience and performance which can meet the needs of discerning video professionals and technical divers.



Limited Warranty

1. Bigblue guarantees the proper operation of this product by the original retail purchaser under normal and intended use.
2. This warranty applies only to the original retail purchaser, which does not apply to commercial or rental use, nor is it transferable to third parties.
3. If the original retail purchaser detects defect in the materials or workmanship, return the product together with proof of purchase indicating the date of purchase to an authorized Bigblue dealer or Bigblue.
4. The warranty covers a period of up to one (1) year from the date of purchase. Warranty for rechargeable battery pack is valid for six (6) months only.
5. This limited warranty is in lieu of all other warranties. No other person or party is authorized to assume for Bigblue any other liability in connection with the sales of this product.
6. This warranty will be voided if the product or any of its parts have been tempered with, repaired, modified, transformed, adapted or damaged without authorization by Bigblue.
7. This warranty does not cover parts subjected to normal wear and tear, including and is not limited to the following: O-rings, battery pack, front glass (surface scratch or damage on impact).
8. This warranty does not cover damages due to impact, use in chlorinated or polluted waters, and extended exposure to heat sources.

Bossk International Company Limited

Tel : (852) 3568 0773
Email : customerservice@bigblue.com.hk
Web : www.bigbluelights.com
www.bigblue.com.hk
MADE IN CHINA Patent Pending





VTL7000P MAX EOS

BACKMOUNT / SIDEMOUNT

7000 lumens WIDE

2900 lumens SPOT

Li ion Rechargeable Battery High Power LED Video / Tech Light with E/O Cord Battery Canister

INSTRUCTION MANUAL




Sidemount (23.8 Ah)



Backmount (23.8 Ah)

Features

- 6 x ultra high intensity LED delivers 7000 lumens, and an 120° perfect even light spot, making it a must for the best video shoot results.
- 3 x ultra high intensity LED delivers 2900 lumens, and an 10° strong penetrating light spot, making it ideal for tech-dive.
- The LEDs are maintenance-free, they guarantee a burn time of 50,000 hours, reducing the need for frequent bulb replacement.
- The 6500K white light reflects the true vibrant colors of the underwater surrounding while diving.
- The six levels power output lets you choose between 100%, 50%, 25% of total brightness for wide beam and narrow beam.
- The push button not only makes it easy to change between the power output levels, but it is also designed to be insulated from all internal parts, eliminating the risk of leakage.
- Li ion rechargeable battery design comes with a smart charger, enabling you to change in a few hours.
- The thermal protection system prevents the light from overheating by automatically cutting off its power in case of prolonged use on land, or exposure to temperatures above 70°C. As soon as the light cools off, power comes back on.
- Built in red LED for viewing shy little creatures and enhancing focusing performance.
- Removable yellow filter to achieve a warmer color tone for video shooting.



Using the rechargeable Li ion battery

- Intended to be used with the custom-made BATCELLEOCANISTER Li ion rechargeable battery pack only.
- Connect with the correct polarity (+ and -) only, incorrect connection can damage the unit.
- Fully charge the batteries before using for the first time.
- Use only the power adapters supplied with the charger. Using incompatible adapters may damage the charger or result in fire or electric shock.
- Charge time will depend on the remaining charge in the battery and the surrounding temperature.
- Do not charge near hot temperature, under direct sunlight, cover the charger with a blanket, or place under heavy pressure. If the temperature is too high, it may cause the battery to leak or rupture.
- When storing or carrying the battery, avoid direct contact with metal objects to avoid short circuit.
- The Li ion battery should not be dropped or be subjected to strong mechanical shock.
- Remove the battery from the light if it is not going to be in use for an extended period of time.
- Do not operate the battery or the charger if it has been damaged or subjected to shock.
- Do not dispose of in fire. Do not heat, deform, solder, disassemble or modify.
- Do not dispose of your rechargeable battery with general household waste. Check with your local collection system for electrical and electronic products.
- Do not short-circuit, overcharge, crush, drop, mutilate, generate with foreign objects, apply reverse polarity, expose to high temperature or disassemble packs and cells.
- Use only lithium-ion cells with a designated protection circuit and approved charger.
- Discontinue using the battery and/or charger if the battery gets excessively warm.
- The electrolyte is highly flammable and battery rupture can cause physical injury.
- Use a foam extinguisher, CO2, dry chemical, powdered graphite, copper powder or soda (sodium carbonate) to extinguish a burning lithium-ion battery cannot be from spreading.
- If the fire of a burning lithium-ion battery cannot be controlled and safe manner.
- External damage, such as being dropped or getting wet, can also cause a lithium-ion battery to fail.

Charging Li ion battery

1. Fully charge the battery before using it first time.
2. Use only the power adapter supplied with the charger.
3. Plug in the charger before you place the battery in the charger.
4. Make sure to connect with the correct polarity. Incorrect connection can damage the unit.
5. The red light on the charger will light up after a short time, indicating charging is taking place. If the red light does not light up, disconnect the battery and re-connect it again. If the red light does not light up after several attempts, the battery does not function.
6. Green light on the charger indicates fully charged battery. The battery should then be disconnected.
7. Charge the battery after each use. It does not have to be discharged before charging. Should charge the battery every month even you don't use it.
8. Do not turn on the light, if the light has turned off due to low battery capacity. Turning on the light with a fully discharged battery can damage the battery.
9. Charge time will depend on the remaining charge in the battery and the surrounding temperature
10. Remove the battery from the light if it is not going to be used for extended period of time

Li ion battery charge and care